

Fitting Flap Type Seal to Round Top Fridge.

Firstly, upon receiving your new seal, check that the new seal profile is similar to the old one, hold the new seal against the new one to make sure it is roughly the same size. If your new seal has been folded for posting you will need to unfold the seal and lay it flat for at least **1 HOUR** in a warm place to settle prior to installation.

Normally when fitting seals it is easier to do half of a door at a time, starting with the top half.

With Round Top Fridges it is generally easier to do the bottom half first (unless you are removing the liner completely from the door).

Remove any items in the door to reduce weight!

Remove screws from bottom half of door, remove old seal and install bottom half of new seal then replace screws, do not tighten too tight.

Now remove the remainder of the screws (top half of the door) and take out remaining old seal.

Offer the new seal up to the top of the door and mark of the section which will be rounded with a pencil.

Carefully “notch out” the sections of the new seal (a notching sample will be included with seal purchase) – this will help the seal bend around the shoulders of the liner and prevent kinking.

Install remaining (top half) of seal to door and replace screws.

Your new seal may be tight at first (old seals have had years to compact and settle in). Many old style doors have latches and strikes that can be adjusted to accommodate the new height of seal.

Close fridge door and leave as long as possible to settle in.

Once complete, send us a picture of your new seal on your round top fridge, fill with beer, stand back and admire your handywork!