

## Fitting Flap Type Seal - With Screws

Firstly, upon receiving your new seal, check that the new seal profile is similar to the old one, hold the new seal against the new one to make sure it is roughly the same size. If your new seal has been folded for posting you will need to unfold the seal and lay it flat for at least **1 HOUR** in a warm place to settle prior to installation. If you have a tall door it is always best to start at the top to attach then install the bottom and work your way up to the top so as not to stretch the seal.

1. Remove all screws from the upper top half of the liner, remove the old seal and replace with new one.
2. Put screws back (push screws through liner and flap of seal). Lightly tighten screws.
3. Do the same with the bottom half of the liner, working your way up from the bottom, making sure corners stay in place.
4. If the door closes smoothly, but there are gaps on the top or bottom corners of handle side, gently try twisting the door into shape, you may need to loosen screws to do this.
5. Check around the whole seal for gaps, again, if there are gaps don't worry, this is normal. To fix these gaps use a heat gun (on low setting) or a hair dryer to gently warm the seal and you should see the gaps closing without any help. KEEP THE HEAT GUN OR HAIR DRYER MOVING, DO NOT CONCENTRATE IN ONE AREA FOR LONG AND DON'T GET TOO CLOSE, THE SEAL WILL MELT IF IT GETS TOO HOT. You can however get the seal almost too hot to touch. If the gap is too big you may need to help close the gap with your fingers. Once the gap has closed the magnet in the seal should keep it closed but you should not open the door until the seal has completely cooled, this could be 10 to 20 minutes.
6. If your seal is catching on the hinge side there are two options to try, firstly, use some talcum powder or corn flour on the frame of the fridge, this will act as a lubricant and allow the seal to slide more easily against the frame. Secondly, some fridge doors are adjustable, you may be able to loosen the bolts holding the top hinge to the fridge and move the door slightly to compensate for a tight seal.